



## Touch-Screen Computers from Accu-Scan!

**Durable, flexible, designed for School Food Service**

### Highlights

- 15.1" Dual Backlit LCD panel - TFT active matrix
- Spill-proof water-resistant structure protects circuitry; allows for easy cleaning
- Software controlled on/off switch to prevent accidental shutdown
- Patented finger-release lever "geared locking mechanism" - easily adjusts the LCD tilt angle
- Security lock prevents unauthorized access to input/output data devices
- LED indicates Power "ON"
- Network interface card is built in
- Accepts all Meal Tracker® input devices
- Windows 98, 2000, XP Pro

### Overview

With its unique space-saving footprint and durability, Accu-Scan's new touch-screen terminal provides *flexibility* and *dependability* demanded by school food service professionals.

Paired with **Meal Tracker® Point of Sale** software, you'll have the state-of-the-art in POS accountability.

Use as the main cafeteria workstation, as a serving terminal, or as both! They can be used both in countertop and wall mount applications . . . talk about flexibility!



For more information, or a demonstration, please call  
**toll-free 888-880-8278 ext. 138 or 140**  
[accu-scan.com](http://accu-scan.com)

# JIVA 5000 Series Touch-Screen Specifications

Max. LCD Resolution	1024 x 768
Brightness	250 nit
Audio Line Output	Standard
LCD Panel	15.1" TFT
CPU	800 MHz
Touch Resolution	1024 x 1024
Secondary Display Interfaces	VGA
Memory	DDR 266, SDRAM x 2 DIMM up to 1 GB
Serial Port	3
Parallel Port	1
USB Port	2
Keyboard Port	1 x PS/2 type
Mouse Port	1 x PS/2 type
LAN Port	10/100 MHz base Ethernet
CD-ROM Port	1
Hard Drive	20 GB
ON/OFF Control	Software controlled for mechanical On/Off
Touch Sensor	Resistive
Tilt Adjustment	From 17.5 to 87.5 degrees
Mounting Option	Table top or wall mount
Touch Control Function	Emulate mouse left/right, double-click
Touch Beep Controls	Sound pitch adjustment, sound enable/disable by software
Power Supply	AC adaptor: Input 100~240V, output DC 12V/60W
Storage Condition	-20°C ~ +60°C, 10%RH ~ 80%RH; non-condensing, maximum wet bulb 28.9°C
Operation Condition	0°C ~ +40°C, 20%RH ~ 80%RH; non-condensing, maximum wet bulb 26°C
Dimension	375mm (W) x 270mm (D) x 380mm (H) 14.8" x 10.6" x 15"
Weight	15.4 lbs (7.0kg)
Operating System Support	Windows 98, 2000, XP Pro